



AGRICULTURAL PRODUCTS

Information & Application Of Use

NON-CLIMB HORSE FENCE

- Terrific for horses
- Strong 2" x 4" mesh design and varying heights prevent horses from stepping through, walking down or getting over the fence
- Non-climb is a woven fence, which allows it to flex on impact preventing injury to horse or fence
- Fence is woven and not welded, so helps resist being broken or eaten
- Has a 2" x 4" mesh design that prevents your goats from getting their heads or hooves stuck in the fence

POULTRY FENCE

- This uniform hexagonal mesh is reinforced with supplemental horizontal wires so that fencing, pens, and barriers stay straight and upright.
- Galvanized before weaving to last longer and resist rust and corrosion.
- Easier to handle because reverse twist weave unrolls flat.
- 20 Gauge steel wire
- Garden and pet enclosures

UTILITY FENCE

- 16 gauge welded steel / galvanized
- Compost confinements
- Ideal for garden enclosures
- Split rail fence backing
- Pens for Small Pets
- Available in 24", 36", 48", and 60" heights

HIGH TENSILE FIELD FENCE

- Keystone's exclusive Red Brand Monarch Knot Acts as a hinge that gives under pressure.
- Vertical wires are individually cut and wrapped for maximum strength and flexibility.
- Plus, fence retains its full height for continuing protection and good looks.
- The Class 3 galvanized wire has a heavier zinc coating, so it's long lasting and durable.
- High tensile woven field fences are lighter weight than traditional fences.

DEER AND WILDLIFE FENCE

- Designed for long term service in forest and wildlife preserves, zoological parks, highway rights of way, and other public and private protected land applications
- Extra high (8' high) galvanized steel wire mesh fence is heavy-duty in both wire gauge and construction
- Class 3 High Tensile 12-1/2 Gauge Galvanized Wire
- Available in 20 Rod (330') Rolls 96" height

WELDED WIRE FENCE

- General purpose fencing
- Offers strength and rigidity for a variety of outdoor projects
- Galvanized wire and solid welded construction gives this fence strength and rigidity
- Available in 2" x 4" mesh, 1" x 2" mesh, or 1" x 1" mesh
- Rolls come in 50' or 100' lengths and come in a variety of heights

HARDWARE CLOTH

- Ideal for garden and animal fencing, signs, or mailboxes
- Ideal for gardens, workshops, and home projects
- 19 gauge wire with heavy zinc coating applied after welding for maximum protection
- Double selvedge wires at top and bottom for extra strength
- Available in two mesh sizes, 2 x 2 and 4 x 4

9-3/4 Gauge - Class 1 Galvanized - 20 Rod Rolls (330')					
	STYLE	HEIGHT	STRANDS	STAY SPACING	WEIGHT PER ROLL
FSL742	742-12-9-3/4	42"	7	12"	115 LBS.
FSL842	842-12-9-3/4	42"	8	12"	208 LBS.
FSL948	948-12-9-3/4	48"	9	12"	240 LBS.
FSL1048	1048-12-9-3/4	48"	10	12"	245 LBS.

9-3/4 Gauge - Class 1 Galvanized - 40 Rod Rolls (660')					
	STYLE	HEIGHT	STRANDS	STAY SPACING	WEIGHT PER ROLL
FSL84240	842-12-9-3/4 - 40	42"	8	12"	416 LBS.
FSL94840	948-12-9-3/4 - 40	48"	9	12"	480 LBS.

9-3/4 Gauge - Class 1 Galvanized - 40 Rod Rolls (660')					
	STYLE	HEIGHT	STRANDS	STAY SPACING	WEIGHT PER ROLL
FSL8423	842-12-9-3/4 - Class 3	42"	8	12"	208 LBS.
FSL9483	948-12-9-3/4 - Class 3	48"	9	12"	240 LBS.
FSL10483	1048-12-9-3/4 -Class 3	48"	10	12"	245 LBS.

HIGH TENSILE SURE-LOCK TIGHT LOCK FARM FENCE

High Tensile Sure-Lock Farm Fence is manufactured with 12-1/2 gauge Class 111 galvanized wire. Line wire tensile of 180 to 210,000 psi increases fence strength while providing the user with an economical fencing alternative. High Tensile Tight Lock Farm Fence is suitable to control livestock, protect crops, and to enclose pastures and compounds.

12-1/2 Gauge – Class 111 Galvanized – 20 Rod Rolls (330')					
	STYLE	HEIGHT	STRANDS	STAY SPACING	WEIGHT PER ROLL
FSLHT8423	842-12-12-1/2	42"	8	12"	107 LBS.
FSLHT94963	949-6-12-1/2	49"	9	6"	184 LBS.
FSLHT9493	949-12-12-1/2	49"	9	12"	130 LBS.
FSLHT10473	1047-12-12-1/2	48"	10	12"	144 LBS.

12-1/2 Gauge – Class 111 Galvanized – 40 Rod Rolls (660')					
	STYLE	HEIGHT	STRANDS	STAY SPACING	WEIGHT PER ROLL
FSL842340	842-12-12-1/2 - 40	42"	8	12"	226 LBS.
FSL949340	948-16-9-3/4 - 40	49"	9	12"	258 LBS.
FSL1047340	1047-12-12-1/2 - 40	48"	10	12"	288 LBS.

HIGH TENSILE SURE-LOCK TIGHT LOCK WILDLIFE FENCE

High Tensile Sure-Lock Wildlife Fence is manufactured with 12-1/2 gauge Class 111 galvanized wire. Line wire breaking strength is at minimum, 1350 lbs, providing a superior strength fence. The combination of strength, durability, Sure-Lock knots, and flexibility, assures a product that provides the ultimate in performance for animal containment. Wildlife Fence Systems are available in styles ranging from five foot to ten foot high.

12-1/2 Gauge – Class 111 Galvanized – 20 Rod Rolls (330')					
	STYLE	HEIGHT	STRANDS	STAY SPACING	WEIGHT PER ROLL
FSLWF2096	2096 – 6 – 12-1/2	96"	20	6"	414 LBS.

12-1/2 – Class 111 Galvanized – 20 Rod Rolls (330')					
	STYLE	HEIGHT	STRANDS	STAY SPACING	WEIGHT PER ROLL
FSLWF1060	1060 – 12 – 12-1/2 – 20	60"	10	12"	303 LBS.

Topper Fence (Extends Fence System Height by 24" - 20 Rod Rolls (330')					
	STYLE	HEIGHT	STRANDS	STAY SPACING	WEIGHT PER ROLL
FSLWF424	424-12-12-1/2"	24"	4	12"	58 LBS.

WATCHMAN SURE-LOCK TIGHT LOCK FENCE

Watchman Sure-Lock Fence is constructed from 9 Gauge class 1 Galvanized Wire. Watchman Fence is suitable for heavy game ranching such as Elk and Buffalo and is used as safety fence on motor speedways.

9 Gauge – Class 1 Galvanized – 200'					
	STYLE	HEIGHT	STRANDS	STAY SPACING	WEIGHT PER ROLL
FSLW5	5'	60"	11	6"	266 LBS.
FSLW6	6'	72"	13	6"	316 LBS.
FSLW7	7'	84"	15	6"	374 LBS.
FSLW8	8'	94"	17	6"	410 LBS.

*** Also Available in 11 Gauge***

Highway Fence – Class 111 Galvanized – 20 Rod Rolls (330') 9 Gauge Top, Bottom & Fill					
	STYLE	HEIGHT	STRANDS	STAY SPACING	WEIGHT PER ROLL
FSL10479	1047-6-9	47"	10	6"	400 LBS.

Highway Fence – Class 1 Galvanized – 20 Rod Rolls (330') High Tensile 12-1/2 Gauge Top & Bottom, 14-1/2 Gauge Fill					
	STYLE	HEIGHT	STRANDS	STAY SPACING	WEIGHT PER ROLL
FSL9396145	939-6-14-1/2	39"	9	6"	99 LBS.
FSL1047145	1047-6-14-1/2	47"	10	6"	116 LBS.
FSL104712145	1047-12-14-1/2	47"	10	12"	90 LBS.